


ECROU NOYE RIVKLE® CYLINDRIQUE LISSE TETE FRAISEE

Modèle
19762

ACIER ZN PASSIVE 400 HBS

BOLLHOFF



RÉFÉRENCES MEMENTO TECHNIQUE

9.0 Rivetage



RIVKLE® BLIND NUT WITH CYLINDRICAL
BODY AND COUNTERSUNK HEAD
PASSIVATED ZINC PLATED 400 HSST

TUERCAS STANDARD CILINDRICO LISSE
CABEZA AVALLENADARIVKLE® ACERO
ZINCADO BLANCO PASSIVATO 400 HBS

RIVKLE® RIVETTO FILETTATO LISCILO TESTA
SVASATA ZINCATO PASSIVATO 400 HBS



OUTIL DE POSE
POUR ECROU
NOYE RIVKLE®
P 2007
Modèle
19911P2007
Page 0 08

Référence	d nominal	Epaisseur e (mm)	Trou H + 0,1/0 (mm)	B (mm)	E (mm)	S (mm)	L (mm)	L2 (mm)
19762OM4.1-2	M4	1-2	6	7,6	1	3,7-e	10	5,4
19762OM5.1,5-4	M5	1,5-4	7	9,6	1,6	6,5-e	14	8
19762OM5.4-6,5	M5	4-6,5	7	9,6	1,6	9-e	17	8
19762OM6.1,5-4	M6	1,5-4	9	11,7	1,6	6,2-e	16	10
19762OM6.4-6,5	M6	4-6,5	9	11,7	1,6	8,7-e	19	10
19762OM8.1,5-4	M8	1,5-4	11	13,5	1,6	7-e	18	11
19762OM8.4-6,5	M8	4-6,5	11	13,5	1,6	9,5-e	21	11