


■ VIS POUR BOIS DUR TETE FRAISEE REDUITE 6 LOBES

Modèle
62326

INOX A2



d nominal	M4	M4,5	M5
k (mm)	3,3	3,8	4,5
dk (mm)	6,2	7	8
Empreinte T	T15	T20	T25

Référence	d x L (mm)
623264X40	4X40
623264,5X50	4,5X50
623264,5X60	4,5X60
623264,5X70	4,5X70

Référence	d x L (mm)
623265X40	5X40
623265X50	5X50
623265X50SEAU	5X50
623265X60	5X60

Référence	d x L (mm)
623265X60SEAU	5X60
623265X70	5X70
623265X80	5X80



RÉFÉRENCES MEMENTO TECHNIQUE

- 11.29 Classification des aciers inoxydables couramment utilisés en boulonnerie-visserie
- 11.23 Tableau de choix des numéros d'embouts et clés
- 11.22 Performance des modes d'entraînement des vis : formes et empreinte NFE 25-031



COUNTERSUNK HEAD SCREW FOR HARD WOOD SIX LOBE RECESS STAINLESS STEEL

TORNILLO PARA MADERA DURA CABEZA AVALLENADA SEIS LOBULADOS INOX A2

VITE PER LEGNO DURO TESTA SVASATA 6 LOBI ACCIAIO INOSSIDABILE A2



EMBOUT
SIX LOBES -
ACIER
Modèle 36040
Page 0 09



PORTE
EMBOUT
MAGNETIQUE
- ACIER
Modèle 36070
Page 0 12